

SPECIFICATIONS	2004 SALE	EEN S281SC
GENERAL	Coupe	Convertible
Curb Weight, lb.	3428	3620
Weight Distribution, F/R	57/43	57/43
Fuel Capacity, gal.	1	5.7
Wheelbase, in.	10	01.3
Track, F/R	59.7	7/61.5
Width	7	' 3.1
Length	18	85.2
Height	52.0	52.2
Trunk Space, cubic ft.	10.8	7.7

ENGINE

Туре	4.6L, 2V, SOHC V-8		
Bore and Stroke	3.60 x 3.60 in.		
Displacement	4.6L, 281C.I.		
Exhaust System	Saleen Stainless, 2.5" Exhaust		
Horsepower	375 hp @ 5800 RPM		
Torque	415 ftlb. @ 3500 RPM		
Fuel	Premium Unleaded 91 Octane		
Saleen Intercooled Supercharger	Saleen Series IV Twin Screw Supercharger, 3.5 inch power tube, 80mm Cast 356-		
	T6 Aluminum Inlet Tube, Saleen Cast 356-T6 Aluminum Manifold, Water-to-Air		
	Intercooler, Saleen PowerFlash Engine Management, 30lb./hr Fuel Injectors		

DRIVETRAIN

Transmission	Saleen Quick Ratio 5-Speed Transmission
8.8 in. Differential 3.27 Ratio	Standard
Saleen MaxGrip	Optional

SUSPENSION

Front	Hybrid Macpherson with Saleen Racecraft system including N2 struts, variable-
I TOTAL	, ,
	rate coil springs mounted on lower control arms, 1.38 in. stabilizer (anti-roll) bar
	with urethane pivot bushings, specially calibrated suspension settings
Rear	Live axle four bar link with variable-rate coil spings on lower trailing arms, Quadra
	Shock System with Saleen Racecraft shocks; stabilizer (anti-roll) bar

BRAKES

Power 4-Wheel ABS Brakes		
10.8 in. Dual Piston Vented Disc (Front)	Standard	
10.5 in. Disc (Rear)		
Saleen ABS 4-Piston Calipers		
13.0 in. Slotted and Vented Disc (Front)	Optional	

WHEELS AND TIRES

Saleen Five Spoke Alloy Wheels		
18 in. x 9 in. Front	Standard	
18 in. x 9 in. Rear	Standard	
18 in. x 10 in. Rear	Optional	
High Performance Pirelli P-Zero Nero		
P255/35ZR18 (Front)	Standard	
P265/35ZR18 (Rear)	Standard	
High Performance Pirelli P-Zero Rosso Upgrade		
P265/35ZR18 (Front)	Optional	
P295/35ZR18 (Rear)	Optional	